

SPECIFICATIONS

3710 TEDDER

MODEL..... 3710 Tedder

DIMENSIONS AND WEIGHTS

Length (Pull Type) ft (m)..... 6.89 (2.10)
Width (Transport) ft (m)..... 6.17 (1.88)
Width (Operating) ft (m)..... 9.75 (2.97)
Height (Transport, Pull Type) ft (m)..... 5.58 (1.7)
Height (Operating) ft (mm) 3.12 (0.95)
Weight lb (kg)..... 468 (213)

MAINFRAME

Type Pull Type or 3 Pt. Mounted
Working Widths ft (m)..... 9.58 (2.92)
PTO Driveline..... 1 3/8" – 6 Spline with Torque Limiter
Maximum Operating Speed mph (km/hr) 9.0 (14.5)
Tires (2)..... 15-6.00 x 6, Ribbed Balloon

ROTORS

Rotor Diameter in (mm)..... 15.8 (400)
 End of Arms in (mm)..... 53.5 (1360)
 To Outside Tooth in (mm) 63.0 (1600)
Number of Rotors 2
Number of Arms per Rotor 6
Number of Double Tines per Rotor..... 6
Number Of Double Tines..... 12
Tine Length in (mm) 15.8 (400)
Tine Diameter in (mm)..... 0.39 (10)
Clearance Under Rotor in (mm) 25.6 (650)
Rotor Speed (At 540 rpm) rpm 189

TRACTOR REQUIREMENTS

Horsepower hp (kW)
 Pull Type 15 (11)
 Three Point Mounted..... 25 (19)
PTO 540
Hydraulics
 Remote Outlets None Required
 Three Point Hitch (Mounted Units) Category I or II

(Specifications and design are subject to change without notice and without liability therefore.)

SPECIFICATIONS

3717 TEDDER

MODEL..... 3717 Tedder

DIMENSIONS AND WEIGHTS

Length (Pull Type) ft (m)..... 8.20 (2.5)
Width (Transport) ft (m)..... 8.20 (2.5)
Width (Operating) ft (m)..... 17.55 (5.35)
Height (Transport, Pull Type) ft (m)..... 8.37 (2.55)
Height (Operating) ft (mm) 3.87 (1.18)
Weight lb (kg)..... 730 (331)

MAINFRAME

Type Pull Type or 3 Pt. Mounted
Working Width ft (m)..... 17 (5.2)
PTO Driveline..... 1 3/8" – 6 Spline with Torque Limiter
Maximum Operating Speed mph (km/hr) 13.0 (21)
Tires (4)..... 15-6.00 x 6, Ribbed Balloon

ROTORS

Rotor Diameter in (mm)..... 15.8 (400)
 To End of Arms in (mm)..... 53.5 (1360)
 To Outside Tooth in (mm) 63.0 (1600)
Number of Rotors 4
Number of Arms per Rotor 6
Number of Double Tines per Rotor..... 6
Number Of Double Tines..... 24
Tine Length in (mm) 15.8 (400)
Tine Diameter in (mm)..... 0.39 (10)
Clearance Under Rotor in (mm) 25.6 (650)
Rotor Speed (At 540 rpm) rpm 189

TRACTOR REQUIREMENTS

Horsepower hp (kW)
 Pull Type 20 (15)
 Three Point Mounted..... 40 (30)
PTO 540
Hydraulics
 Remote Outlets..... One Double Acting Remote Valve (With Hyd Wing Fold)
 Three Point Hitch (Mounted Units)..... Category I or II

(Specifications and design are subject to change without notice and without liability therefore.)